

**PRODUCT USE DATA SHEET**

Generic Sheet for  
Stage Waterfall  
0589-T1-0410

Projects a column of Silver and/or Gold sparks. Various Times, distances and effects are available as labelled. They also produce smoke and hot gas.

<b>CAD</b>	ID N°: <b>XI/5015/195/6</b>	Serial N°: <b>00487</b>	Title: <b>Gerb</b>
<b>CE</b>	Reg: <b>0589-T1-0410</b>	Category: <b>T1 - Outdoor</b>	Type: <b>DROPPING EFFECT</b>
	Class/UN N°: <b>1.4S/0432</b>	Batch N°: <b>N/A</b>	Max NEC: <b>17 (Grams/unit)</b>

**ONLY FOR USE BY PERSONS AGED 18 YEARS OR OVER**

**FS4 SAFETY FIRST**

- SC001 T1 users may only use these articles for theatrical purposes within Stage, film and television productions, as well as within music or show productions.
- sc002 All T1 users must abide by the stated Minimum Safety Distance on the product and given below.\*
- sc004 Always test a sample of the product to be used to confirm suitability to the job and the venue.\*
- sc018 Do not fire these products in an unsuitable confined space or an area with poor ventilation.\*
- sc005 Typically T2 users should allow at least 1.5 times the Stated Directional Effect (or calculated Sound distance) as a safety margin when firing towards (or near) persons, scenery or flammable objects in the effects designed orientation.\*
- sc008 These products project hot sparks, Directionally, sometimes a considerable distance with a possible report and some smoke and localised hot gas.
- sc020 These products are designed to be fired from a height above a stage or controlled area, etc. They are normally fitted or hung from a truss or similar. For other uses contact Wells Fireworks for further advice.\*
- sc041 These products are primarily designed for indoor use and only function correctly in still or near still air conditions - If used outdoors expect a loss of performance especially if fired in moving air.
- sc014 Do not fire directly above any persons, scenery or flammable objects\*.
- sc038 Any spark resistant covering used must rend, erode or melt instantly on ignition. Any form of additional covering may have a dramatic effect on a products performance.
- sc037 This product will take ignition freely from hot sparks or other free ignition sources. Avoid ALL such sources of accidental initiation. If damaged do NOT use.
- SC033 Ensure the products are secured firmly, using suitable holders, fittings or containers as necessary. Always avoid undue force when rigging products as this may damage the units.
- SC029 Bridge Wire Resistance - 1.0Ω (Std. Deviation ± 0.09Ω). Max Test Current 40mA. Max No-Fire Current 300mA. Min Firing Current 1.0A. Recommended Nominal Firing Current 1.25A.
- SC046 \* Please Call or Email Wells Fireworks for further details if you intend to use these effects in a way other than intended by the manufacturer.

**FS24 Product Specific T2 Data for use by Persons With Specialist Knowledge**

FS29	Effect Code	CE Variant	A (m)	B		C (m)	D (m)	T (m)	T1 Safety Distances	
				dB	@m				Effect	Radial
*	GFVS0000WH1070	10s x 7m (Silver)	9	69.8	12	0	0	2	12	3
*Example Product Shown - see specific Sheet for accurate data										

FS26 *Key - A: Effect distance. B: Sound Pressure level including the measuring distance. C: Hazardous debris distance.*  
 FS27 *D: Information on incandescent particles returning to the level from which the device was fired. T: Radial effect distance*  
 FS28 *T1 Safety Distances: These are the recommended minimum safe use distances for amateur use.*  
 sc047 *\* Wells Fireworks assumes no liability for the misuse of this product. It is up to the purchaser to ensure the safe use and suitability by Test Firings prior to the performance or public admittance.*